

# SHEEP DEHIDER



This machine mainly used for sheep and goat skin removed, The machine compare is more convenient for controlling and weight is less compare the old technology, the gear motor and air compress systems teamwork, as normal this machine used for small and middle size sheep and goat abattoir, The machine working with less noise and working condition more stated.

## Specifications

|                            |                                          |
|----------------------------|------------------------------------------|
| Pneumatic Cylinder         | 1600mm                                   |
| Out Size                   | 950*530*2600mm (L*W*H)                   |
| Roller speed               | 1.6-16m/min                              |
| Rated Voltage              | 380V/ 3P / 50HZ                          |
| Power                      | 1.5Kw                                    |
| Maximum operating pressure | 0.6MPa                                   |
| Material                   | Stainless steel and hot galvanized steel |



### HEADQUARTER

PT ARSI INDO GRAHA  
INDONESIA

+6281270762750

info@arsiindograha.com

www.arsiindograha.com

### GLOBAL OFFICE

RC INDO GROUP LIMITED  
RWANDA

+250793885693

info@rcrwanda.com

www.rcrwanda.com

ARSYI GLOBAL L.L.C-FZ  
DUBAI

+971507169760

info@arsyi.com

www.arsyi.com

# SHEEP DEHIDER



Mesin ini terutama digunakan untuk menguliti domba dan kambing. Mesin ini dibandingkan dengan teknologi lama, lebih mudah dioperasikan dan memiliki bobot yang lebih ringan. Motor gear dan sistem kompresor udara bekerja secara bersamaan untuk menjalankan mesin. Mesin ini umumnya digunakan di rumah potong hewan (RPH) domba dan kambing berukuran kecil hingga menengah. Mesin bekerja dengan tingkat kebisingan yang rendah dan memiliki kondisi kerja yang lebih stabil.

## Spesifikasi

|                        |                                          |
|------------------------|------------------------------------------|
| Silinder Pneumatic     | 1600 mm                                  |
| Ukuran Luar            | 950 x 530 x 2600 mm (L x W x H)          |
| Kecepatan Roller       | 1.6 - 16 m/min                           |
| Besar Tegangan         | 380 V / 3 P / 50 HZ                      |
| Daya                   | 1.5 kW                                   |
| Tekanan Kerja Maksimum | 0.6 Mpa                                  |
| Bahan                  | Stainless steel and hot galvanized steel |



### HEADQUARTER

PT ARSI INDO GRAHA  
INDONESIA

+6281270762750  
info@arsiindograha.com  
www.arsiindograha.com

### GLOBAL OFFICE

RC INDO GROUP LIMITED  
RWANDA

+250793885693  
info@rcrwanda.com  
www.rcrwanda.com

ARSYI GLOBAL L.L.C-FZ  
DUBAI

+971507169760  
info@arsyi.com  
www.arsyi.com