CIRCULAR BREAKING SAW
MODEL SEC 280-04



The Jarvis Model SEC 280-04 -
electric powered circular breaking saw.

JARVIS

- The SEC 280-04, with a 4 inch (102 mm) depth of cut, is ideally suited for:
  - Beef: cutting chucks, shoulders, ribs, forequarters, hindquarters, chine bones, briskets and loins.
- Sealed, 2.25 hp electric motor for ultimate performance.
- Specially designed handles for easy operation.
- Features electric or mechanical braking.
- Smooth surface construction for easy cleaning and optimum hygiene.
- Anti-tie down controls for operator safety.
- Meets national and international requirements for hygiene and safety.



SMOOTH - POWERFUL - RUGGED

AIG GROUP

JARVIS®

HEADQUARTER
PT ARSI INDO GRAHA
INDONESIA
+6281270762750
info@arsiindograha.com
www.arsiindograha.com

GLOBAL OFFICE
RC INDO GROUP LIMITED
RWANDA
+250793885693
info@rcrwanda.com
www.rcrwanda.com

ARSYI GLOBAL L.L.C-FZ
DUBAI
+971507169760
info@arsyi.com
www.arsyi.com

CIRCULAR BREAKING SAW
MODEL SEC 280-04

Specifications		
Drive		Electric
Model SEC 280-04		
Motor Power	2.25 hp	1678 W
Operating Voltage		575 / 460 /380 / 230 / 208 V, 3 phase, 60 Hz 415 / 380 / 220 / 115 / 42 V, 3 phase, 50 Hz
Blade Speed		
50 Hz		1350 rpm
60 Hz		1650 rpm
Control Handles		Electric Dual Anti-tie Down or One Trigger (CE)
Brake		Electric (DC) or Mechanical
Blade Diameter	11.0 in	280 mm
Cutting Depth (maximum)	4.0 in	102 mm
Overall Length	27 in	686 mm
Weight	40 lbs	18.1 kg
Vibration	less than 108 dB	< 0.25 m / sec^2
Noise (one meter from tool)		less than 80 dB

Equipment Selection and Accessories	Order Number
Model Sec 280-04*	
42 V, 3 phase, 50 Hz* dual triggers with electric brake	4004075
42 V, 3 phase, 50 Hz single trigger with mechanical brake	4004147
115 V, 3 phase, 50 Hz* dual trigger with electric brake	4004067
115 V, 3 phase, 50 Hz single trigger with mechanical brake	4004155
208 V, 3 phase, 60 Hz* dual triggers with electric brake	4004079
208 V, 3 phase, 60 Hz single trigger with mechanical brake	4004156
220 V, 3 phase, 50 Hz* dual triggers with electric brake	4004068
220 V, 3 phase, 50 Hz single trigger with mechanical brake	4004157
230 V, 3 phase, 60 Hz* dual triggers with electric brake	4004069
230 V, 3 phase, 60 Hz single trigger with mechanical brake	4004148
380 V, 3 phase, 50 Hz* dual triggers with electric brake	4004070
380 V, 3 phase, 50 Hz* single trigger with mechanical brake	4004153
380 V, 3 phase, 60 Hz* dual triggers with electric brake	4004071
380 V, 3 phase, 60 Hz single trigger with mechanical brake	4004158
415 V, 3 phase, 50 Hz* dual triggers with electric brake	4004072
460 V, 3 phase, 60 Hz* dual triggers with electric brake	4004073
460 V, 3 phase, 60 Hz single trigger with mechanical brake	4004149
575 V, 3 phase, 60 Hz* dual triggers with electric brake	4004074
Blades *Please specify blade preference when ordering.*	
11.0 in / 280 mm diameter, 150 teeth	1023288
11.0 in / 280 mm diameter, Skip Tooth - 78 teeth	1023388
11.0 in / 280 mm diameter, 72 teeth	1023393
11.0 in / 280 mm diameter, noise reduction - random teeth	1023295
Balancer	4042035

** Other configurations available: please specify voltage, hertz and blade preference when ordering.*

AIG GROUP

JARVIS®

HEADQUARTER
PT ARSI INDO GRAHA
INDONESIA
+6281270762750
info@arsiindograha.com
www.arsiindograha.com

GLOBAL OFFICE
RC INDO GROUP LIMITED
RWANDA
+250793885693
info@rcrwanda.com
www.rcrwanda.com

ARSYI GLOBAL L.L.C-FZ
DUBAI
+971507169760
info@arsyi.com
www.arsyi.com

CIRCULAR BREAKING SAW
MODEL SEC 280-04



The Jarvis Model SEC 280-04 - gergaji pemecah bundar bertenaga listrik

- The SEC 280-04, dengan kedalaman potongan 4 inch (102 mm) , sangat sesuai untuk:
  - Daging sapi : potongan chucks, shoulders (bahu), ribs (iga), forequarters (bagian depan), hindquarters (bagian belakang), chine bones (tulang punggung), brisket dan loins (bagian pinggang).
- Motor electrik 2,25 hp yang tertutup rapat untuk menghasilkan kinerja optimal.
- Tuas alat yang dirancang khusus untuk memudahkan pengoperasian.
- Alat ini dilengkapi dengan sistem pengereman electrik atau pengereman mekanis.
- Permukaan konstruksi alat halus untuk memudahkan pembersihan dan menjaga higienitas optimal.
- Anti-tie down controls untuk keselamatan operator.
- Memenuhi persyaratan higienitas dan keselamatan nasional dan internasional.



HALUS - KUAT - TANGGUH

AIG GROUP

JARVIS®

HEADQUARTER
PT ARSI INDO GRAHA
INDONESIA
+6281270762750
info@arsiindograha.com
www.arsiindograha.com

GLOBAL OFFICE
RC INDO GROUP LIMITED
RWANDA
+250793885693
info@rcrwanda.com
www.rcrwanda.com

ARSYI GLOBAL L.L.C-FZ
DUBAI
+971507169760
info@arsyi.com
www.arsyi.com

CIRCULAR BREAKING SAW
MODEL SEC 280-04

Spesifikasi

Drive		Elektrik
Model SEC 280-04		
Daya Motor	2.25 hp	1678 W
Tegangan Operasional		575 / 460 /380 / 230 / 208 V, 3 phase, 60 Hz 415 / 380 / 220 / 115 / 42 V, 3 phase, 50 Hz
Kecepatan Blade		
50 Hz		1350 rpm
60 Hz		1650 rpm
Tuas Pengendali		Elektrik, Dual Anti-tie Down atau One Trigger (CE)
Rem		Elektrik (DC) atau Mekanik
Diameter Blade	11.0 in	280 mm
Kedalaman Potongan (maksimal)	4.0 in	102 mm
Panjang Keseluruhan	27 in	686 mm
Berat	40 lbs	18.1 kg
Getaran	less than 108 dB	< 0.25 m / sec^2
Kebisingan (satu meter dari alat)		less than 80 dB

Pilihan Peralatan dan Aksesori		Nomor Pemesanan
Model Sec 280-04*		
42 V, 3 phase, 50 Hz*	trigger ganda dengan pengereman elektrik	4004075
42 V, 3 phase, 50 Hz	trigger tunggal dengan pengereman mekanik	4004147
115 V, 3 phase, 50 Hz*	trigger ganda dengan pengereman elektrik	4004067
115 V, 3 phase, 50 Hz	trigger tunggal dengan pengereman mekanik	4004155
208 V, 3 phase, 60 Hz*	trigger ganda dengan pengereman elektrik	4004079
208 V, 3 phase, 60 Hz	trigger tunggal dengan pengereman mekanik	4004156
220 V, 3 phase, 50 Hz*	trigger ganda dengan pengereman elektrik	4004068
220 V, 3 phase, 50 Hz	trigger tunggal dengan pengereman mekanik	4004157
230 V, 3 phase, 60 Hz*	trigger ganda dengan pengereman elektrik	4004069
230 V, 3 phase, 60 Hz	trigger tunggal dengan pengereman mekanik	4004148
380 V, 3 phase, 50 Hz*	trigger ganda dengan pengereman elektrik	4004070
380 V, 3 phase, 50 Hz*	trigger tunggal dengan pengereman mekanik	4004153
380 V, 3 phase, 60 Hz*	trigger ganda dengan pengereman elektrik	4004071
380 V, 3 phase, 60 Hz	trigger tunggal dengan pengereman mekanik	4004158
415 V, 3 phase, 50 Hz*	trigger ganda dengan pengereman elektrik	4004072
460 V, 3 phase, 60 Hz*	trigger ganda dengan pengereman elektrik	4004073
460 V, 3 phase, 60 Hz	trigger tunggal dengan pengereman mekanik	4004149
575 V, 3 phase, 60 Hz*	trigger ganda dengan pengereman elektrik	4004074
Blades	*Harap tentukan pilihan blade saat melakukan pemesanan.*	
11.0 in / 280 mm diameter, 150 teeth		1023288
11.0 in / 280 mm diameter, Skip Tooth - 78 teeth		1023388
11.0 in / 280 mm diameter, 72 teeth		1023393
11.0 in / 280 mm diameter, mengurangi kebisingan - random teeth		1023295
Balancer		4042035

**** Konfigurasi lainnya tersedia. Harap tentukan tegangan, frekuensi, dan pilihan blade saat melakukan pemesanan.***

AIG GROUP

JARVIS®

HEADQUARTER
PT ARSI INDO GRAHA INDONESIA
+6281270762750
info@arsiindograha.com
www.arsiindograha.com

GLOBAL OFFICE
RC INDO GROUP LIMITED RWANDA
+250793885693
info@rcrwanda.com
www.rcrwanda.com

ARSYI GLOBAL L.L.C-FZ DUBAI
+971507169760
info@arsyi.com
www.arsyi.com