

SHEEP HOCK CUTTER

Model 425-16



**The Jarvis Model 425-16 -
hydraulically powered hock cutter
for sheep.**

JARVIS

- The 425-16 is best suited for sheep hock cutting before fleece removal. It is also suitable for beef tail removal and hog hock cutting.
- Compact for easy maneuverability; robust for long, trouble-free operation.
- Super fast cutting cycle combined with high cutting force means high performance for the most demanding applications.
- Available with pistol grip or in straight handles for optimum operator comfort.
- Anti-tie down controls for operator safety.
- Constructed from corrosion resistant materials for optimum hygiene.
- Meets national and international requirements for hygiene and safety.



POWERFUL - ROBUST- COMPACT

AIG GROUP

JARVIS®

HEADQUARTER

PT ARSI INDO GRAHA
INDONESIA

☎ +6281270762750

✉ info@arsiindograha.com

🌐 www.arsiindograha.com

GLOBAL OFFICE

RC INDO GROUP LIMITED
RWANDA

☎ +250793885693

✉ info@rcrwanda.com

🌐 www.rcrwanda.com

ARSYI GLOBAL L.L.C-FZ
DUBAI

☎ +971507169760

✉ info@arsyi.com

🌐 www.arsyi.com

SHEEP HOCK CUTTER

Model 425-16

Specifications

Drive	Hydraulic	
Model 425-16		
Capacity		720 / hour
Cutting Cycle Time		1.0 sec
Cutting Force	1300 lbf	5.78 kN
Control Handle		
Air / Dual Anti-tie Down	50 psi	3.4 bar
Blade Opening	3.7 in	94 mm
Overall Length		
With Pistol Grip Handle (4025075)	18 in	457 mm
With In-Line Handle (4025072)	25 in	635 mm
Weight	20 lbs	9 kg
Hydraulic Power Unit		
Motor Power	5.0 hp	3729W
Operating Voltage	460 / 230 V, 3 phase, 60 Hz	
	other voltages and frequencies available	
Hose Length	16 ft	4.9 m
Oil Capacity	20 gal	76 L
Oil Viscosity at 100° F / 40° C	200 SUS	46 ISO
Overall Dimensions (with heat exchanger) (l x w x h)	34 x 24 x 28 in 864 x 610 x 711 mm	
Overall Dimensions (without heat exchanger) (l x w x h)	31.5 x 25.4 x 29.9 in 800 x 645 x 760 mm	
Weight (without oil)	250 lbs	113 kg

Equipment Selection and Accessories

Order Number

Model 425 -16	with straight handles	4025072
	with pistol grip and "D" handles	4025075
Hydraulic Power Unit without heat exchanger		
with control box and hoses, 460 / 230 V, 3 phase, 60 Hz		4027266
Hydraulic Power Unit without heat exchanger		
with control box and hoses, 440 / 415 / 380 / 220 V, 50 Hz		4027216
Hydraulic Power Unit with heat exchanger		
with control box and hoses, 460 / 230 V, 3 phase, 60 Hz		4027307
Balancer		4042045
Blade	standard	1023366
	right side tool	1023460



HEADQUARTER

PT ARSI INDO GRAHA
INDONESIA

+6281270762750

info@arsiindograha.com

www.arsiindograha.com

GLOBAL OFFICE

RC INDO GROUP LIMITED
RWANDA

+250793885693

info@rcrwanda.com

www.rcrwanda.com

ARSYI GLOBAL L.L.C-FZ
DUBAI

+971507169760

info@arsyi.com

www.arsyi.com

SHEEP HOCK CUTTER MODEL 425-16



Jarvis Model 425-16 adalah alat pemotong bagian kaki belakang domba yang bertenaga hidrolik.

JARVIS

- Model 425-16 sangat cocok digunakan untuk pemotongan kaki belakang domba, sebelum proses pelepasan bulu. Alat ini juga dapat digunakan untuk pemotongan ekor sapi dan kaki belakang babi.
- Desainnya compact sehingga mudah digunakan dan dipindahkan, namun tetap memiliki konstruksi yang kuat untuk penggunaan jangka panjang dengan minim gangguan.
- Kecepatan siklus pemotongan yang sangat tinggi, dikombinasikan dengan tenaga potong yang besar, membuat alat ini mampu memberikan kinerja maksimal untuk berbagai pekerjaan berat.
- Tersedia pilihan pistol grip atau in straight handles untuk memberikan kenyamanan terbaik bagi operator.
- Dilengkapi sistem kontrol pengaman anti-tie down untuk meningkatkan keselamatan operator saat bekerja.
- Dibuat menggunakan material yang tahan terhadap korosi sehingga lebih higienis.
- Memenuhi standar nasional dan internasional terkait persyaratan kebersihan dan keselamatan kerja.



KUAT - KOKOH - COMPACT



HEADQUARTER

PT ARSI INDO GRAHA
INDONESIA

+6281270762750

info@arsiindograha.com

www.arsiindograha.com

GLOBAL OFFICE

RC INDO GROUP LIMITED
RWANDA

+250793885693

info@rcrwanda.com

www.rcrwanda.com

ARSYI GLOBAL L.L.C-FZ
DUBAI

+971507169760

info@arsyi.com

www.arsyi.com

SHEEP HOCK CUTTER MODEL 425-16

Spesifikasi

Drive	Hidrolik	
Model 425-16		
Kapasitas		720 / hour
Waktu Siklus Pemotongan		1.0 sec
Tenaga Pemotongan	1300 lbf	5.78 kN
Pegangan Kontrol		
Udara/ Dual Anti-tie Down	50 psi	3.4 bar
Jarak Buka Blade	3.7 in	94 mm
Panjang Keseluruhan		
dengan Pistol Grip Handle (4025075)	18 in	457 mm
dengan In-Line Handle (4025072)	25 in	635 mm
Berat	20 lbs	9 kg
Hydraulic Power Unit		
Daya Motor	5.0 hp	3729W
Tegangan Operasi	460 / 230 V, 3 phase, 60 Hz	
	Tersedia pilihan tegangan dan frekuensi lainnya	
Panjang Selang	16 ft	4.9 m
Kapasitas Oli	20 gal	76 L
viskositas Oli pada 100° F / 40° C	200 SUS	46 ISO
Dimensi keseluruhan (dengan heat exchanger) (P x L x T)	34 x 24 x 28 in	864 x 610 x 711 mm
Dimensi keseluruhan (tanpa heat exchanger) (P x L x T)	31.5 x 25.4 x 29.9 in	800 x 645 x 760 mm
Berat (tanpaoli)	250 lbs	113 kg

Pilihan Peralatan dan Aksesori

Nomor Pemesanan

Model 425 -16	dengan straight handles	4025072
	dengan pistol grip dan "D"	4025075
Hydraulic Power Unit tanpa heat exchanger	handles	
dengan control box and hoses, 460 / 230 V, 3 phase, 60 Hz		4027266
Hydraulic Power Unit tanpa heat exchanger		
dengan control box and hoses, 440 / 415 / 380 / 220 V, 50 Hz Hydraulic		4027216
Power Unit dengan heat exchanger		
dengan control box and hoses, 460 / 230 V, 3 phase, 60 Hz		4027307
Balancer		4042045
Blade	standard	1023366
	right side tool	1023460



HEADQUARTER

PT ARSI INDO GRAHA
INDONESIA

+6281270762750

info@arsiindograha.com

www.arsiindograha.com

GLOBAL OFFICE

RC INDO GROUP LIMITED
RWANDA

+250793885693

info@rcrwanda.com

www.rcrwanda.com

ARSYI GLOBAL L.L.C-FZ
DUBAI

+971507169760

info@arsyi.com

www.arsyi.com