

CIRCULAR BREAKING SAW MODEL SEC 280-04



The Jarvis Model SHC 140 and SHC 165 - hydraulic powered general purpose breaking saws.

JARVIS

- The SEC 280-04, with a 4 inch (102 mm) depth of cut, is ideally suited for:
 - Beef: cutting chucks, shoulders, ribs, forequarters, hindquarters, chine bones, briskets and loins.
- Sealed, 2.25 hp electric motor for ultimate performance.
- Specially designed handles for easy operation.
- Features electric or mechanical braking.
- Smooth surface construction for easy cleaning and optimum hygiene.
- Anti-tie down controls for operator safety.
- Meets national and international requirements for hygiene and safety.



SMOOTH - POWERFUL - RUGGED

AIG GROUP

JARVIS®

HEADQUARTER

PT ARSI INDO GRAHA
INDONESIA

☎ +6281270762750

✉ info@arsiindograha.com

🌐 www.arsiindograha.com

GLOBAL OFFICE

RC INDO GROUP LIMITED
RWANDA

☎ +250793885693

✉ info@rcrwanda.com

🌐 www.rcrwanda.com

ARSYI GLOBAL L.L.C-FZ
DUBAI

☎ +971507169760

✉ info@arsyi.com

🌐 www.arsyi.com

CIRCULAR BREAKING SAW

MODEL SEC 280-04

Specifications		
Drive	Electric	
Model SEC 280-04		
Motor Power	2.25 hp	1678 W
Operating Voltage	575 / 460 /380 / 230 / 208 V, 3 phase, 60 Hz 415 / 380 / 220 / 115 / 42 V, 3 phase, 50 Hz	
Blade Speed		
50 Hz		1350 rpm
60 Hz		1650 rpm
Control Handles	Electric Dual Anti-tie Down or One Trigger (CE)	
Brake	Electric (DC) or Mechanical	
Blade Diameter	11.0 in	280 mm
Cutting Depth (maximum)	4.0 in	102 mm
Overall Length	27 in	686 mm
Weight	40 lbs	18.1 kg
Vibration	less than 108 dB	< 0.25 m / sec ²
Noise (one meter from tool)		less than 80 dB
Equipment Selection and Accessories		Order Number
Model Sec 280-04*		
42 V, 3 phase, 50 Hz* dual triggers with electric brake		4004075
42 V, 3 phase, 50 Hz single trigger with mechanical brake		4004147
115 V, 3 phase, 50 Hz* dual trigger with electric brake		4004067
115 V, 3 phase, 50 Hz single trigger with mechanical brake		4004155
208 V, 3 phase, 60 Hz* dual triggers with electric brake		4004079
208 V, 3 phase, 60 Hz single trigger with mechanical brake		4004156
220 V, 3 phase, 50 Hz* dual triggers with electric brake		4004068
220 V, 3 phase, 50 Hz single trigger with mechanical brake		4004157
230 V, 3 phase, 60 Hz* dual triggers with electric brake		4004069
230 V, 3 phase, 60 Hz single trigger with mechanical brake		4004148
380 V, 3 phase, 50 Hz* dual triggers with electric brake		4004070
380 V, 3 phase, 50 Hz* single trigger with mechanical brake		4004153
380 V, 3 phase, 60 Hz* dual triggers with electric brake		4004071
380 V, 3 phase, 60 Hz single trigger with mechanical brake		4004158
415 V, 3 phase, 50 Hz* dual triggers with electric brake		4004072
460 V, 3 phase, 60 Hz* dual triggers with electric brake		4004073
460 V, 3 phase, 60 Hz single trigger with mechanical brake		4004149
575 V, 3 phase, 60 Hz* dual triggers with electric brake		4004074
Blades <i>Please specify blade preference when ordering.</i>		
11.0 in / 280 mm diameter, 150 teeth		1023288
11.0 in / 280 mm diameter, Skip Tooth - 78 teeth		1023388
11.0 in / 280 mm diameter, 72 teeth		1023393
11.0 in / 280 mm diameter, noise reduction - random teeth		1023295
Balancer		4042035

* Other configurations available: please specify voltage, hertz and blade preference when ordering.



JARVIS®

HEADQUARTER

PT ARSI INDO GRAHA
INDONESIA

+6281270762750

info@arsiindograha.com

www.arsiindograha.com

GLOBAL OFFICE

RC INDO GROUP LIMITED
RWANDA

+250793885693

info@rcrwanda.com

www.rcrwanda.com

ARSYI GLOBAL L.L.C-FZ
DUBAI

+971507169760

info@arsyi.com

www.arsyi.com

CIRCULAR BREAKING SAW MODEL SEC 280-04



Jarvis Model SHC 140 and SHC 165 - breaking saws serbaguna bertenaga hydraulic.

JARVIS

- The SEC 280-04, dengan kedalaman potongan 4 inch (102 mm) , sangat sesuai untuk:
 - Daging sapi : potongan chucks, shoulders (bahu), ribs (iga), forequarters (bagian depan), hindquarters (bagian belakang), chine bones (tulang punggung), brisket dan loins (bagian pinggang).
- Motor elektrik 2,25 hp yang tertutup rapat untuk menghasilkan kinerja optimal.
- Tuas alat yang dirancang khusus untuk memudahkan pengoperasian.
- Alat ini dilengkapi dengan sistem pengereman elektrik atau pengereman mekanis.
- Permukaan konstruksi alat halus untuk memudahkan pembersihan dan menjaga higienitas optimal.
- Anti-tie down controls untuk keselamatan operator.
- Memenuhi persyaratan higienitas dan keselamatan nasional dan internasional.



HALUS - KUAT - TANGGUH

AIG GROUP

JARVIS®

HEADQUARTER

**PT ARSI INDO GRAHA
INDONESIA**

☎ +6281270762750

✉ info@arsiindograha.com

🌐 www.arsiindograha.com

GLOBAL OFFICE

**RC INDO GROUP LIMITED
RWANDA**

☎ +250793885693

✉ info@rcrwanda.com

🌐 www.rcrwanda.com

**ARSYI GLOBAL L.L.C-FZ
DUBAI**

☎ +971507169760

✉ info@arsyi.com

🌐 www.arsyi.com

CIRCULAR BREAKING SAW MODEL SEC 280-04

Spesifikasi

Drive	Elektrik	
Model SEC 280-04		
Daya Motor	2.25 hp	1678 W
Tegangan Operasional	575 / 460 / 380 / 230 / 208 V, 3 phase, 60 Hz 415 / 380 / 220 / 115 / 42 V, 3 phase, 50 Hz	
Kecepatan Blade		
50 Hz		1350 rpm
60 Hz		1650 rpm
Tuas Pengendali	Elektrik, Dual Anti-tie Down atau One Trigger (CE)	
Rem	Elektrik (DC) atau Mekanik	
Diameter Blade	11.0 in	280 mm
Kedalaman Potongan (maksimal)	4.0 in	102 mm
Panjang Keseluruhan	27 in	686 mm
Berat	40 lbs	18.1 kg
Getaran	less than 108 dB	< 0.25 m / sec ²
Kebisingan (satu meter dari alat)		less than 80 dB

Pilihan Peralatan dan Aksesori

Nomor Pemesanan

Model Sec 280-04*		
42 V, 3 phase, 50 Hz* trigger ganda dengan pengereman elektrik		4004075
42 V, 3 phase, 50 Hz trigger tunggal dengan pengereman mekanik		4004147
115 V, 3 phase, 50 Hz* trigger ganda dengan pengereman elektrik		4004067
115 V, 3 phase, 50 Hz trigger tunggal dengan pengereman mekanik		4004155
208 V, 3 phase, 60 Hz* trigger ganda dengan pengereman elektrik		4004079
208 V, 3 phase, 60 Hz trigger tunggal dengan pengereman mekanik		4004156
220 V, 3 phase, 50 Hz* trigger ganda dengan pengereman elektrik		4004068
220 V, 3 phase, 50 Hz trigger tunggal dengan pengereman mekanik		4004157
230 V, 3 phase, 60 Hz* trigger ganda dengan pengereman elektrik		4004069
230 V, 3 phase, 60 Hz trigger tunggal dengan pengereman mekanik		4004148
380 V, 3 phase, 50 Hz* trigger ganda dengan pengereman elektrik		4004070
380 V, 3 phase, 50 Hz* trigger tunggal dengan pengereman mekanik		4004153
380 V, 3 phase, 60 Hz* trigger ganda dengan pengereman elektrik		4004071
380 V, 3 phase, 60 Hz trigger tunggal dengan pengereman mekanik		4004158
415 V, 3 phase, 50 Hz* trigger ganda dengan pengereman elektrik		4004072
460 V, 3 phase, 60 Hz* trigger ganda dengan pengereman elektrik		4004073
460 V, 3 phase, 60 Hz trigger tunggal dengan pengereman mekanik		4004149
575 V, 3 phase, 60 Hz* trigger ganda dengan pengereman elektrik		4004074
Blades Harap tentukan pilihan blade saat melakukan pemesanan.		
11.0 in / 280 mm diameter, 150 teeth		1023288
11.0 in / 280 mm diameter, Skip Tooth - 78 teeth		1023388
11.0 in / 280 mm diameter, 72 teeth		1023393
11.0 in / 280 mm diameter, mengurangi kebisingan - random teeth		1023295
Balancer		4042035

* Konfigurasi lainnya tersedia. Harap tentukan tegangan, frekuensi, dan pilihan blade saat melakukan pemesanan.



JARVIS®

HEADQUARTER

PT ARSI INDO GRAHA
INDONESIA

+6281270762750

info@arsiindograha.com

www.arsiindograha.com

GLOBAL OFFICE

RC INDO GROUP LIMITED
RWANDA

+250793885693

info@rcrwanda.com

www.rcrwanda.com

ARSYI GLOBAL L.L.C-FZ
DUBAI

+971507169760

info@arsyi.com

www.arsyi.com