

BLEEDING CONVEYOR LINE



Which is used for hanging and conveying live cattle for killing, bleeding, and hoof removal.

Motor Power	3KW
Distance of the hanging frame	160cm
Material	Iron cast rail hanger Stainless steel orbit
Length	X meter

Remark: The system includes the following devices (the tension device is used to tighten the overhead conveyor rail when it becomes loose).

Driving Device

Tension device

Rotator device



JARVIS®

HEADQUARTER

PT ARSI INDO GRAHA
INDONESIA

+6281270762750

info@arsiindograha.com

www.arsiindograha.com

GLOBAL OFFICE

RC INDO GROUP LIMITED
RWANDA

+250793885693

info@rcrwanda.com

www.rcrwanda.com

ARSYI GLOBAL L.L.C-FZ
DUBAI

+971507169760

info@arsyi.com

www.arsyi.com

BLEEDING CONVEYOR LINE



Alat ini digunakan untuk menggantung dan mengangkut sapi hidup selama proses penyembelihan, penirisan darah dan pelepasan kuku.

Daya Motor	3 kW
Jarak rangka gantung	160 cm
Material	Rail hanger berbahan iron cast Orbit conveyor berbahan stainless steel
Panjang	X meter

Catatan: Sistem pada alat ini mencakup beberapa perangkat (device) (the tension device digunakan untuk mengencangkan overhead conveyor rail ketika rail menjadi kendur).

Driving Device (Perangkat penggerak)

Tension device (Perangkat penegang)

Rotator device (Perangkat pemutar)



JARVIS®

HEADQUARTER

PT ARSI INDO GRAHA
INDONESIA

☎ +6281270762750

✉ info@arsiindograha.com

🌐 www.arsiindograha.com

GLOBAL OFFICE

RC INDO GROUP LIMITED
RWANDA

☎ +250793885693

✉ info@rcrwanda.com

🌐 www.rcrwanda.com

ARSYI GLOBAL L.L.C-FZ
DUBAI

☎ +971507169760

✉ info@arsyi.com

🌐 www.arsyi.com