

SHEEP V RESTRAINER



Which mainly used to convey living sheep/goat for hanging

Specifications

Rated Voltage	380V/ 3P/50HZ
Power	2.2Kw
Capacity	100-4000sheep/goat per hour
Length	L mm
Material	Hot galvanized steel main support PE conveyed belt Stainless steel cover



HEADQUARTER

PT ARSI INDO GRAHA
INDONESIA

+6281270762750
info@arsiindograha.com
www.arsiindograha.com

GLOBAL OFFICE

RC INDO GROUP LIMITED
RWANDA

+250793885693
info@rcrwanda.com
www.rcrwanda.com

ARSYI GLOBAL L.L.C-FZ
DUBAI

+971507169760
info@arsyi.com
www.arsyi.com

SHEEP V RESTRAINER



Alat ini digunakan terutama untuk mengangkat domba/kambing hidup ke tempat penggantungan.

Spesifikasi

Besar Tegangan	380V / 3P/ 50 HZ
Daya	2.2 kW
Kapasitas	100 - 4000 domba/kambing per jam
Panjang	L mm
Bahan	Penopang utama terbuat dari hot galvanized steel Sabuk konveyor berbahan PE (polietilena) Penutup terbuat dari stainless steel



HEADQUARTER

PT ARSI INDO GRAHA
INDONESIA

+6281270762750
info@arsiindograha.com
www.arsiindograha.com

GLOBAL OFFICE

RC INDO GROUP LIMITED
RWANDA

+250793885693
info@rcrwanda.com
www.rcrwanda.com

ARSYI GLOBAL L.L.C-FZ
DUBAI

+971507169760
info@arsyi.com
www.arsyi.com